

## AN ASSEMBLY COMPRISING AN ELECTRICAL ELEMENT

h' &gt;

The present invention relates to an assembly comprising an electrical element, such as a coil, and especially to an assembly more easily assembled. Assemblies of this type are typically used for so-called receivers for hearing aids or sound generators for e.g. mobile telephones.

Normally, such assemblies are assembled by providing e.g. the coil, which has an electrical conductor which has to be contacted from the outside of the housing of the assembly in a manner where separate electrical conductors are provided for providing this electrical connection and which have to be connected to the coil. This operation is highly labour intensive, and the present invention relates to a manner of making this operation easier.

In a first aspect, the invention relates to an assembly comprising:

- an electrical element adapted to provide or receive power and/or an electrical signal, the element comprising at least one input or output for the power and/or signal,
- a housing, the electrical element being positioned within the housing,

the housing comprising an opening/hole or an indentation at an inner surface thereof,

the assembly further comprising at least one projection being attached to the electrical element or engaging the electrical element,

the projection being adapted to be introduced into the opening or indentation when the electrical element is positioned within the housing.

Thus, providing this projection and opening/indentation, the electrical element may be kept in place by the interaction of these elements. Compared to the prior art manners of assembling this assembly, this manner is less labour intensive.

Providing indentations in the housing will provide the positioning of the electrical element but not access to the projections from outside the housing.

A preferred manner is one wherein the housing comprises an opening and wherein the projection is electrically conducting and is electrically connected to one of the inputs/outputs of the electrical element. In this manner, not only may the projection/hole aid in maintaining the electrical element in position within the housing, but the input/output of the electrical element may also be contacted from the outside via this projection. In this manner, not only positioning/maintaining of the electrical element is provided but also easy electrical contact to the electrical element without having to provide other electrical connections from outside the housing to the element inside the housing.

- 10 Alternative to the providing of a hole would be to provide a housing at least part of which is electrically conducting for the projection to obtain electrical contact to the surroundings via or through the housing.

One manner of providing this type of projection is to provide a solder bump into which is soldered e.g. an electrical conductor connected to or forming an input/output. An alternative to the solder bump would be e.g. a pressure contact.

Especially when the housing comprises two openings and where the assembly further comprises two projections, another projection in addition to the above projection, being attached to the electrical element or engaging the electrical element, wherein the other projection is electrically conducting and is electrically connected to the other of the input/output of the electrical element, is the connection to the electrical element facilitated. Alternatively, the other of the input/output may be attached to the housing or at least part thereof which is electrically conducting in order for the connection to that input/output to take place via the housing.

It may be preferred that the electrical element is enclosed within a container, the at least one projection being provided at a surface thereof. The container may comprise a material wherein the electrical element is at least partly cast-in.

Then, the at least one projection may be displaceable in relation to the electrical element or at least part of the container. In that situation, the electrical element and projections may be adapted to be snap-fitted into the housing by the operation of the displaceable projections and the holes or indentations of the housing.

In the present context, a compressible projection may be made of a resilient material in order for a surface thereof to be displaceable in relation to other parts thereof - and this resilient material may be covered by an electrically conductive material if the electrical conductivity of the resilient material itself is not sufficient. Alternatively, a non-compressible projection may  
5 be made displaceable using any type of means, such as springs or resilient materials.

More generally, the electrical element or container preferably comprises a surface at least substantially opposite to a surface comprising a projection, these two surfaces corresponding to corresponding inner surfaces of the housing, where an opening or  
10 indentation is provided in the inner surface of the housing corresponding to the surface of the electrical element or container having the projection.

Thus, no glue or other fastening means need be provided in order to maintain the electrical element in place. Another advantage of this is seen in situations where it is desired to  
15 remove the electrical element from the housing. This removal is extremely difficult when the electrical element has been e.g. fastened using glue.

Especially when providing the electrical element in the container - such as when at least partly casting it into a material - may the electrical element obtain physical dimensions more  
20 easily adaptable to the clicking in action and further for supporting or stabilizing the housing.

The providing of the container may more easily provide the electrical element with outer dimensions similar to the inner dimensions of at least part of the housing such that if the projection(s) is/are provided at one side thereof, that surface and an opposite surface thereof  
25 preferably at least substantially correspond to opposite inner surfaces of the housing. In any situation, the resilient action of the projection preferably ensures that the opposite surface engages the corresponding side of the housing during insertion of the electrical element (optionally in the container) in the housing and when the projection is forced into the housing until engaging or being positioned within the opening or indentation.

30 One preferred assembly of the above type is one, wherein:

- the electrical element comprises a coil comprising at least one coiled electrical conductor having two ends,
- the at least one electrical input and/or output comprising an end of the coil.

An assembly of that type may be for use as a receiver/loud speaker for a hearing aid or a mobile telephone.

5 Naturally, the advantages of the invention and especially the clicking action and the access to the projections through holes in the housing will be obtained independently of the type and nature of the electrical element. Thus, this electrical element may be of any type, such as one chosen from the group consisting of: electrical circuitry, battery, coil, sensor, etc.

10 An external carrier holding one or more electrically conductive paths may be connected to the projections whereby electrical connection may be established between the assembly and the surroundings. This external carrier may e.g. be a circuit board or a flex-print.

In yet another aspect, the invention relates to a sub assembly for use in the above assembly, the sub assembly comprising:

- 15
- an electrical element adapted to provide or receive power and/or an electrical signal, the element comprising at least one input or output for the power and/or signal,
  - one or more projections displaceably attached to or engaging the electrical element and each being electrically connected to an input/output of the electrical element.

20 Preferably, the electrical element is provided within a container and where the projection(s) is/are provided at a surface thereof. This the container may be made of a resilient material and/or may be provided by at least partly casting-in the electrical element in a casting material.

25 In a further aspect, the invention relates to an assembly comprising:

- an electrical element adapted to provide or receive power and/or an electrical signal, the element comprising at least one input or output for the power and/or signal,
- a housing, the electrical element being positioned within the housing,

30 the housing comprising an opening/hole,

the at least one input or output for the power and/or signal being adapted to be introduced into the opening/hole when the electrical element is positioned within the housing.

Preferably, the electrical element may comprise two electrical inputs and/or outputs. In addition, the assembly may comprise a carrier comprising two electrically conducting paths, each of said two electrically conducting paths being electrically connected to one of the inputs or outputs of the electrical element.

5

In a further aspect, the invention relates to an assembly comprising:

- an electrical element adapted to provide or receive power and/or an electrical signal, the element comprising two inputs or two outputs for the power and/or signal,
- 10 - a housing, the electrical element being positioned within the housing,

the housing comprising two plugs at an outer surface thereof,

- the two plugs being electrically connected with the two inputs or two outputs when the
- 15 electrical element is positioned within the housing.

In a further aspect, the invention relates to a method of assembling an assembly, the method comprising:

- 20 1) providing an electrical element adapted to provide or receive power and/or an electrical signal, the element comprising at least one input or output for the power and/or signal,
- 2) providing a housing having at least one opening or one indentation at an inner surface thereof,
- 25 3) providing one or more projections attached to or engaging the electrical element, the projections being displaceable in relation to the electrical element,
- 4) positioning the electrical element within the housing in a manner so that each of the one or more projections extends into one or the at least one opening or indentation.

- 30 Again, in order to facilitate electrical connection to the electrical element, step 2) preferably comprises providing a housing with at least one opening, and step 3) preferably comprises providing one or more projections each being electrically connected to an input/output of the electrical element.

Most preferably, step 2) comprises providing a housing with two openings, and step 3) comprises providing two projections each being electrically connected to an input/output of the electrical element.

- 5 Again, to facilitate the positioning of the coil in the housing, preferably step 4) comprises positioning the electrical element within the housing using a clicking action by the one or more projections in the at least one opening.

The method may comprise the further step of positioning, before step 4), the electrical  
10 element within a container, and step 3) may comprise providing the one or more projections at a surface of the container. This further step may comprise providing the container by at least partly casting-in the electrical element in a material.

In a preferred embodiment, the method may be one, wherein:

15

- step 1) comprises providing a coil comprising at least one coiled electrical conductor having two ends,
- step 3) comprises providing two projections each being electrically connected to an end of the conductor.

20

In a further aspect, the present invention relates to an assembly comprising:

- an electrical element adapted to provide or receive power and/or an electrical signal, the element comprising at least one input or output for the power and/or signal,
- 25 - a housing, the electrical element being positioned within the housing,

the housing comprising an opening/hole or an indentation at an inner surface thereof,

the assembly further comprising at least one projection forming part of the electrical element,  
30 said at least one projection being adapted to be introduced into the opening or indentation when the electrical element is positioned within the housing.

In the following, a preferred embodiment of the invention will be described with reference to the drawing wherein:

35

Fig. 1 is a cross sectional view of the preferred embodiment of the invention,

Fig. 2 is an elevational side view of a view of the embodiment of Fig. 1, where half of the receiver has been cut away,

Fig. 3 is an elevational top view of the receiver without the top part of the housing,

Fig. 4 is a side view of a receiver with e.g. a flex-print attached to the projection,

Fig. 5 is an elevational side view of a view of the embodiment of Fig. 4,

Fig. 6 is an elevational side view as Fig. 5 without half of the receiver cut away, and now with two conductive stripes connected to the projections,

Fig. 7 is an elevational view of a complete receiver with two conductive stripes connected to the projections,

Fig. 8 shows a receiver with a circuit board or flex-print attached to the housing,

Fig. 9 shows an alternative embodiment to the arrangement shown in Fig. 8, and

Fig. 10 also shows an alternative embodiment to the arrangement shown in Fig. 8.

Figs. 1 and 2 illustrate a preferred receiver for use in a hearing aid. This receiver receives electrical impulses from a signal source, typically comprising a microphone or other transducer, and generates the sound for the user to hear.

This receiver comprises a housing 1 having a sound output 2, where the sound is generated by a membrane 4 connected via a pin 6 to a so-called armature 8 which is a U-shaped (or optionally E-shaped) metallic member. The armature 8 extends through a coil 10 and magnets 12. The magnets are placed within the magnet housing 20. *not shown*

One end of the armature 8 is fixed to the magnet housing 20, where the other arm thereof is movably positioned inside the coil 10 and magnets 12.

The overall function of the receiver is that the coil 10 receives electrical impulses via two solder bumps 14, which are connected to an electrical conductor in the coil 10. This will generate a magnetic field in the coil 10 which travels in the armature 8 to the magnets 12

which will then make the "free" end of the armature 8 travel toward one magnet away from the other magnet, and vice versa, whereby the pin 6 will cause the membrane 4 to move in the same direction as the free end of the armature.

- 5 The surroundings of the membrane 4 comprise a lower compartment enclosing the coil 10, magnets 12, armature 8, etc, and an upper compartment interconnected with the output 2 via a conduit 16. Thus, the movements of the membrane 4 generate sound output by the output 2. Normally, the membrane will have a so-called pressure-compensating hole.
- 10 The housing 1 has two openings 18 (of which one is illustrated) into which (and through) the solder bumps 14 extend. In this manner, electrical connection to the coil is obtained simply via these solder bumps 14.

The manufacture of the receiver comprises firstly preparing the coil by coiling an electrical  
15 conductor. Thereafter, the coil is cast-in in a suitable material on the surface of which the ends of the electrical conductor are soldered into solder bumps 14.

- The solder bumps 14 are displaceably mounted so that they may be displaced in a direction toward the coil 10 in order to obtain a clicking action when mounting the coil 10 in the  
20 housing 1.

Subsequently, the magnets 12 are fastened to magnet holders 20 and subsequently attached to the cast-in coil 10. Then, the armature 8 is provided.

- 25 The subsequent step is the providing of the housing 1 with the openings 18 and the membrane 4 therein, where after the assembly of the coil 10, magnets 12, holders 20, solder bumps 14, and armature 8 is provided in the housing 1 so that the solder bumps 14 extend into the openings 18 so that a clicking action is obtained and the assembly is at least substantially fixed within the housing. Finally, the pin 6 is provided and attached.

30

Fig. 3 shows a receiver as shown in Figs. 1 and 2 disassembled - i.e. without the top part of the housing 1.

- Figs. 4 and 5 show side-views of the preferred receiver, where e.g. a flex-print, a circuit  
35 board of e.g. Kapton 24 or any other carrier carrying an electrical conductor 25 is attached to projection 14 whereby electrical contact is established between the conductor on flex-print



25 and one of the ends of coil 10. The conductor 25 may thereby establish electrical connection between one end of coil 10 and other electronic devices/components within the hearing aid.

- 5 Figs. 6 and 7 illustrate the situation where each projection 14 is electrically connected to the conductor 25 on the carrier whereby e.g. signals/power generated by external components may be provided to coil 10. Fig. 6 shows the received without the upper part of the housing, whereas Fig. 7 shows the assembled receiver - i.e. with the complete housing.
- 10 Figs. 8 and 9 show a receiver with a small circuit board of Kapton or a flex-print 26 positioned on the outside of the housing 1. As seen, the ends of the coil (wires 27 in opening ww) are connected directly to circuit board or flex-print 26 via solder bumps 28. On the circuit board or flex-print one or more gold stripes 29 ensures that electrical connection may be established to external electrical devices or components. The receiver shown in Fig. 8 and 9
- 15 may be used as a plug. The receiver shown in Fig. 9 may also be electrically connected to the surroundings via wires soldered to contact pads 30. Block 31 is positioned between contact pads 28 and gold stripes 29 in Fig. 8. This block prevents the solder material to run, and thereby cover, gold stripes 29.
- 20 Fig. 10 shows a receiver with connectors/plugs 32 positioned on the back of housing 1. With these connectors, the receiver may be used as a plug whereby the receiver may be easily and conveniently connected to external components, such as external circuit boards, electronic components or other external electronic devices (not shown). The connectors are typically fabricated in a flex-print material.